

Luméa Shell Mosaic Tile Specification

A decorative tile suitable for walls including wet areas

Sizes	25x25mm pieces 11 sheets per m2 5kg
	15x15mm pieces 11 sheets per m2 4kg
Thickness	2.3mm +/-0.2mm including poly-fabric backing
Construction	Solid shell pieces glued on 300 x 300 mm poly-fabric backing.
Finish	Buff Polished.
Colours	Made from natural shell types: NZ abalone (Paua), Black Mother of pearl, Freshwater Mother of Pearl.
Cutting	Cut with a diamond blade tile wet saw or dry masonry blade.
Installation	Install with 2 pack epoxy adhesive and grouts ¹ or standard ceramic tile adhesives.
	Because the shell is thinner than a normal mosaic, we recommend a 4-5mm packing strip or sheet is first glued to the wall before adhering the shell mosaics. To get the right volume of adhesive applied using a $1.5-2.0\mathrm{mm}$ notched trowel.
Limitations	 Use only non-abrasive cleaners. As a natural product, shade, pattern and minor size variation are inherent characteristics. Not suitable for salt or chlorine swimming pools. Not suitable for under water immersion Recommended for shower walls but not shower floors.

These recommendations are a general guide only. For more specific details please contact us.

_

 $^{^{\}rm 1}$ e.g Litokol's 'Litoelastic' and 'Starlike' products or Mapei's 'Kerapoxy' and 'Ultracolour Plus'