

Luméa Veneer Panel Specification

A decorative panel suitable for interior walls.

Sizes	Custom panel sizes up to 2400 x 1200 mm
Thickness	7mm +/-0.2mm
Size tolerance	+/- 0.5%
Construction	Shell Veneer specially bonded to MDF, Acrylic or Signex backing and coated with a urethane finish.
Finish	Urethane-acrylic gloss finish. A unique high performance two component finish coat with excellent resistance to abrasion, moisture, petroleum solvents and mineral and vegetable oils, alkalis and acids. UV stable. Can be recoated if necessary.
Colours	Made from natural shell types: White mother of pearl, NZ abalone (Paua), Black Mother of pearl, Freshwater Mother of Pearl Range of colour tints available of the above shells.
Cutting	Cut with a diamond blade tile wet saw, NOT a tile scribe. Seal any cuts with clear lacquer.
Limitations	<ul style="list-style-type: none"> - Not suitable for places where intense heat may occur, such as fire surrounds, above oven hobs or on benches. - Use only non-abrasive cleaners. - As a natural product, shade, pattern and minor size variation are inherent characteristics. - Not suitable for salt or chlorine swimming pools. - Not suitable for permanent wet areas. - Not recommended below the shower line in of shower.

These recommendations are a general guide only. For more specific details please contact us.